

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets

(11) Publication number: **0 402 298 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**(45) Date of publication of patent specification :  
07.07.93 Bulletin 93/27(51) Int. Cl.<sup>5</sup>: **B23K 26/08, H01S 3/11**(21) Application number: **90500051.9**(22) Date of filing: **04.06.90**(54) **A system for marking moving objects by laser beams.**(30) Priority: **07.06.89 ES 8901979**(43) Date of publication of application :  
12.12.90 Bulletin 90/50(45) Publication of the grant of the patent :  
07.07.93 Bulletin 93/27(84) Designated Contracting States :  
**AT BE CH DE DK ES FR GB GR IT LI LU NL SE**(56) References cited :  
**PATENT ABSTRACTS OF JAPAN vol. 7, no. 174 (M-223), 21 June 1983; & JP-A-58053444 (NIPPON DENKI K.K.) 30.03.1983**(56) References cited :  
**IEEE JOURNAL OF QUANTUM ELECTRONICS vol. QE-23, no. 12, December 1987, pages 2252-2257, New York, US; P.C. AMUNDSEN et al.: "Low-Loss LiNbO<sub>3</sub> Q Switches: Compensation of Acoustically-Induced Refractive Index Variations"**(73) Proprietor: **CODILASER S.A.**  
**Numancia 43**  
**E-08240 Manresa (Barcelona) (ES)**(72) Inventor: **Sans Ravelat, Ramon**  
**Plaça Canlgo 5**  
**E-08211 Castellar del Vallès Barcelona (ES)**(74) Representative: **Curell Sunol, Jorge et al**  
**c/o Dr. Ing. M. Curell Sunol I.I. S.L. Passeig de Gràcia 65 bis**  
**E-08008 Barcelona (ES)****EP 0 402 298 B1**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

The invention relates to a system for marking moving objects by laser beams, comprising a source emitting laser beams along a path.

With increasing frequency, the packages or the products themselves have to be marked with data indicating a date, a lot number, an expiry date or other detail which is only known as from a particular moment in time, such as when the product has been packaged or when the product itself was prepared. This requirement relating to the time of marking prevents its prior inclusion in the label print, in the package print or, for example, in the mould for final preparation of the product.

Furthermore, the production, packaging or the like frequently proceeds at a very high rate whereby marking with conventional means would involve a very considerable loss of time.

As a result of the above circumstances, recourse has already been had to laser beams for the said marking operation, on the basis that said laser beams may produce a large amount of energy at the point of impingement. Nevertheless, the generally known systems are based on the insertion of a mask between the laser beam source and the area to be marked. A mask is a device which only allows the beams to pass through interstices defining the signs to be marked. Nevertheless, these masks provide images which are not variable in time and to be able to produce different images, it is necessary to have a plurality of masks available, the appropriate disposal of which is controlled by a stepper motor, with a long time of passage from one letter to another of about 200 milliseconds. The time of passage between letters is understood to be the time which has to elapse between one alphanumeric character and the next one for the process to be correct.

On the other hand, there is known one property of the germanium crystal making it capable of modifying its refractive index depending on the frequency of a received sound signal. To achieve these modifications, there is adapted a transducer of a highly conductive material which performs the function of adapting the germanium crystal to a sound signal, i.e., the speed of sound (5,500 m/s) within the crystal.

One application of this property is known with respect to the configuration of a laser generator. This configuration is basically as follows:

A constant wavelength photon generator means, such as a low pressure plasma tube with a gas mixture ( $\text{CO}_2$ ,  $\text{N}_2$ , He), is taken and an electric field is created therein, producing a photon beam. This photon beam is guided in a cavity formed by two mirrors, one partly reflective and the other 100% reflective.

When the accumulated light energy is sufficiently high, a laser emission occurs through the partly reflective mirror.

To produce a pulsed laser beam, there is inserted within the laser cavity in the direction of the photon beam a germanium crystal with a transducer which when it is excited with a radio frequency signal causes a deviation of the photon beam path, interrupting the laser emission.

When the radio frequency signal is interrupted, the photon beam path is restored, producing a laser emission again. It should be noted that during the time the beam is interrupted there is a considerable increase of energy within the cavity, producing a high energy laser pulse when the emission is restored.

Independently of the above, it is an object of the invention take advantage of the aforesaid property of the germanium crystal, situated outside the aforesaid cavity (extracavity) for a moving objects marking system.

This object is achieved by a system which is characterized in that there is inserted in the laser beam path an extracavity optical deflector comprising a germanium crystal and a transducer adapted to convert radio frequency signals into sound waves suitable for exciting said germanium crystal; in that there being also a switching unit comprising a series of at least five fixed frequency oscillators, the frequency of each oscillator being different from that of the others, the switching unit comprising also an electronic switch situated at the outlet of each oscillator having a switching time of less than 3 microseconds; and in that a control unit is selecting at all times one of said switches to connect at any time one of said oscillators to said transducer.

The system to which the foregoing paragraph refers, therefore, is based on causing successive previously programmed different frequencies to reach said transducer; each different frequency produces a different refractive index in the germanium crystal and obviously, a different refraction (deflection) of the incident beams corresponds to each refractive index.

After substantial trials, it has been determined that the optimum working frequencies of the germanium crystal with its transducer are in the radio frequency band (for example 70 MHz) and it is possible to obtain a band width of 20 MHz at  $\pm 3$  decibels.

As stated above, for the system of the invention, the optical deflector must be accompanied by appropriate electronic equipment allowing each of the deflections to be controlled at all times.

The said electronic equipment has been designed on the basis of a series of fixed frequency oscillators, switched at high speed, whereby a frequency modulated signal is obtained and there corresponds to each of the frequencies a dot which is subsequently used to form the laser image.

By varying the switching of the different frequencies it is possible to create alphanumeric characters and any character capable of being formed by a longitudinal matrix of dots, that is, at least twenty different

there is the code of the alphanumeric character to be marked which is the one processed by the non volatile storage (PROM). At the outlet of the PROM there is a binary code indicating the switches to be accessed and those which are not, as well as the time of access or actuation of the corresponding switch, which takes place through the line 19 extending to the switching unit 7. Access is had only when the count output line 18 coincides with the corresponding bit of the code generator by the PROM.

The speed meter 11 acts in two ways. The first place, it modifies the time base of subunit 13 over the line 20 and, in the second place, it delivers a binary code of n bits over the line 21 to the microprocessor 12 for modification and correction of the general work time. The speed meter 11 may be connected to a display 22 which shows the speed of travel (i.e. in metres per minute) of the objects to be marked.

#### Claims

1. A system for marking moving objects by laser beams, comprising a source emitting laser beams along a path (2), characterized in that there is inserted in said path (2) an extracavity optical deflector comprising a germanium crystal (1) and a transducer (4) adapted to convert radio frequency signals into sound waves suitable for exciting said germanium crystal (1); in that there being also a switching unit (7) comprising a series of at least five fixed frequency oscillators, the frequency of each oscillator being different from that of the others, the switching unit (7) comprising also an electronic switch situated at the outlet of each oscillator having a switching time of less than 3 microseconds; and in that a control unit (8) is adapted to select at all times one of said switches to connect at any time one of said oscillators to said transducer (4).
2. The system of claim 1, characterized in that the frequency of each of said fixed frequency oscillators is in the radio frequency band, having a band width of 20 MHz.
3. The system of any one of the previous claims, characterized in that it comprises a linear radio frequency amplifier (6) receiving the signal from the fixed frequency oscillators and transmitting it to said transducer (4).
4. The system of claim 3, characterized in that said amplifier (6) has a 50 W output, a 600 mW input and a 50 ohm output impedance.
5. The system of any one of the previous claims, characterized in that said control unit (8) comprises

a microprocessor (12) and a non volatile storage containing a character generator (14).

6. The system of claim 5, characterized in that to form the characters to be marked said microprocessor (12) is controlled by a programme having input-output protocols for performing the switching with an external computer.
7. The system of claim 6, characterized in that said switching is effected through an interface circuit (10).
8. The system of any one of the previous claims, characterized in that it comprises a measuring means (11) of the speed of the moving objects to be marked.
9. The system of claim 8, in which the moving objects are conveyed by a production line, characterized in that said speed measuring means (11) is associated with said production line.

#### Patentansprüche

1. System zum Kennzeichnen sich bewogender Objekte durch Laserstrahlen, das eine Quelle umfaßt, die Laserstrahlen entlang eines Weges (2) emittiert, dadurch gekennzeichnet, daß in dem genannten Weg (2) ein außerhalb des Hohlraums befindlicher optischer Deflektor eingesetzt wird, der ein Germaniumkristall (1) und einen Wandler (4) umfaßt, der angepaßt ist, um Radiofrequenzsignale in Schallwellen umzuwandeln, die zum Anregen des genannten Germaniumkristalls (1) geeignet sind; daß es außerdem eine Schalteinheit (7) gibt, die eine Serie von wenigstens fünf Festfrequenz-Oszillatoren umfaßt, wobei die Frequenz jedes Oszillators von der der anderen verschieden ist, wobei die Schalteinheit (7) außerdem einen elektronischen Schalter mit einer Schaltzeit von weniger als 3 Mikrosekunden umfaßt, der am Ausgang eines jeden Oszillators angeordnet ist; und daß eine Steuereinheit (8) angepaßt ist, um immer einen der genannten Schalter auszuwählen, um zu jeder Zeit einen der genannten Oszillatoren mit dem genannten Wandler (4) zu verbinden.
2. System nach Anspruch 1, dadurch gekennzeichnet, daß die Frequenz jedes der genannten Festfrequenz-Oszillatoren im Radiofrequenzband mit einer Bandbreite von 20 MHz liegt.
3. System nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß es einen linearen Radiofrequenz-Verstärker (6) umfaßt, der

das Signal von den Festfrequenz-Oszillatoren empfängt und es zu dem genannten Wandler (4) überträgt.

4. System nach Anspruch 3, dadurch gekennzeichnet, daß der genannte Verstärker (6) einen 50 W-Ausgang, einen 600 mW-Eingang und eine Ausgangsimpedanz von 50 Ohm hat. 5
5. System nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß die genannte Steuereinheit (8) einen Mikroprozessor (12) und einen Permanentenspeicher, der einen Zeichengenerator (14) enthält, umfaßt. 10
6. System nach Anspruch 5, dadurch gekennzeichnet, daß der genannte Mikroprozessor (12) von einem Programm mit Ein-Ausgabe-Protokollen zum Ausführen des Schaltens mit einem externen Rechner gesteuert wird, um die anzubringenden Zeichen zu bilden. 15
7. System nach Anspruch 6, dadurch gekennzeichnet, daß das genannte Schalten durch eine Schnittstellenschaltung (10) bewirkt wird. 20
8. System nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß es eine Meßeinrichtung (11) für die Geschwindigkeit der zu kennzeichnenden sich bewegenden Objekte umfaßt. 25
9. System nach Anspruch 8, bei dem die sich bewegenden Objekte von einer Produktionslinie befördert werden, dadurch gekennzeichnet, daß die genannte Meßeinrichtung (11) für die Geschwindigkeit mit der genannten Produktionslinie in Verbindung steht. 30

#### Revendications

1. Système destiné au marquage d'objets en déplacement par faisceaux ou rayons laser comprenant une source émettant des faisceaux laser le long d'un trajet ; caractérisé en ce qu'une unité de commutation (7) est insérée dans le trajet et comprend un déflecteur optique situé à l'extérieur d'une cavité comprenant un cristal au germanium et un transducteur (4) apte à convertir des signaux haute fréquence en ondes sonores pouvant exciter le cristal au germanium ; en ce qu'il est également prévu une unité de commutation (7) comprenant une série d'au moins cinq oscillateurs de fréquence fixe ; la fréquence de chaque oscillateur étant différente de celle des autres, l'unité de commutation (7) comprenant également un commutateur électronique situé à la sor- 55

tie de chaque oscillateur dont le temps de commutation est inférieur à 3 microsecondes ; et en ce qu'une unité de commande (8) est apte à sélectionner à tout moment l'un des commutateurs pour connecter à tout moment l'un des oscillateurs au transducteur (4).

2. Système selon la revendication 1, caractérisé en ce que la fréquence de chacun des oscillateurs de fréquence fixe est dans la bande haute fréquence avec une largeur de bande de 20 MHz.
3. Système selon l'une quelconque des revendications précédentes, caractérisé en ce qu'il comprend un amplificateur haute fréquence linéaire (6) recevant le signal en provenance des oscillateurs à fréquence fixe et le transmettant au transducteur (4).
4. Système selon la revendication 3, caractérisé en ce que l'amplificateur (6) possède une sortie de 50 W, une entrée de 600 mW et une impédance de sortie de 50 ohms.
5. Système selon l'une quelconque des revendications précédentes, caractérisé en ce que l'unité de commande (8) comprend un microprocesseur (12) et une mémoire non volatile contenant un générateur de caractères (14).
6. Système selon la revendication 5, caractérisé en ce que pour former les caractères à marquer, le microprocesseur (12) est commandé par un programme ayant des protocoles entrée-sortie pour effectuer la commutation avec un ordinateur extérieur.
7. Système selon la revendication 6, caractérisé en ce que la commutation s'effectue par un circuit d'interface (10).
8. Système selon l'une quelconque des revendications précédentes, caractérisé en ce qu'il comprend un moyen de mesure (11) de la vitesse des objets en déplacement à marquer.
9. Système selon la revendication 8, dans lequel les objets en déplacement sont acheminés par une ligne de production, caractérisé en ce que les moyens de mesure de la vitesse (11) sont associés à la ligne de production.




FIG. 1




FIG. 2